

INSTALLATION INSTRUCTIONS KK-K9-FAN OPTIONAL FAN FOR K-9 TRANSPORTATION SYSTEMS

HARDWARE:

OTY	DESCRIPTION

- 1 95 CFM 12 Volt Boxer Fan
- 2 Grill guard
- 4 $8-32 \times \frac{1}{2}$ " Phillips Machine Screw
- 4 8-32-x ³/₄"Phillips Machine Screw
- 8 8-32 Keps Nuts
- 1 Wire Kit

PRM97422 PRM97473 GSM33110 GSM33111 GSM30027 HS-WK-2

PART#

INSTALLATION:

- 1. Fan location to be determined by installer/customer.
- 2. The fan is designed to mount in many various locations. It can be simply mounted on the upper perforated section or a hole can be cut out in the ceiling or lower wall.
- 3. After location is determined, the fan and housing will go on the exterior side of the K9 compartment. Drill (4) 3/16" mounting holes and bolt assembly.
- 4. Wire to fan switch and 12 volt power source.



Consolidator^{*} • Kwik-Raze^{*} • Collins Dynamics^{*} • Kwik-Kit^{**} PrisonerTransports • K-9Transports 75 Jacksonville Rd • P.O. Box 2099 • Warminster, PA 18974 • 800.524.9900 / 215.957.0720(P) • 215.957.0729 (F) www.Havis.com